

General

Number of cylinders	4
Displacement, total	4,76 liters [290,7 cu. in]
Firing order	1-3-4-2
Bore	108 mm [4,25 in]
Stroke mm	130 mm [5,12 in]
Compression ratio	17,6:1

Performance

	25% load	50% load	75% load	100% load	Overload 110% load	
ISO Standard Power	81 kW [110 hp]	20,3	40,5	60,8	81	89,1
Torque	430 Nm [318 lbf ft]	104	210	318	430	475
Mean piston speed	7,8 m/s [25,6 ft/sec]					
Effective mean pressure	1,13 Mpa [165 psi]	0,27	0,55	0,84	1,13	1,25
Max combustion pressure	Mpa [psi]	7,1	8,2	9,2	10,5	11,1

Engine noise emission

Measured sound power Lw at no load	87 dB(A)	
Measured sound power Lw	dB(A)	90,5

Unsilenced exhaust noise emission

Data calculated as sound pressure Lp. Assumed microphone distance 1m.	dB(A)	108
---	-------	-----

Lubrication system

Lubricating oil consumption at ISO Standard Power	liter/h [US Gal/h]	0,05
Lubricating oil system capacity including filters	liters [US Gal]	13

Fuel system

Specific fuel consumption	g/kWh [lb/hph]	255	219	217	222	225
Total fuel flow	liter/h [US Gal/h]				450	
Maximum return flow	liter/h [US Gal/h]					
Feed pump pressure	kPa [in H2 O]				500	
Feed pump max suction head	m				1	
Max allowable back pressure in fuel return line	kPa [H2 O]				50	

Intake system

Air consumption, (at 27oC)	m3/min [cu.ft/min]	4,53	5,05	5,77	6,6	6,9
----------------------------	--------------------	------	------	------	-----	-----

Max permissible air intake restriction

kPa [in H2 O]

2,5

Exhaust system

Heat rejection to exhaust

kW [BTU/min]

16,4

26,7

38,6

51,8

57,7

Exhaust gas temperature after turbine

oC [oF]

205

280

340

385

400

Max allowable back pressure in exhaust line

kPa [H2 O]

3

Exhaust gas flow at Exhaust gas temperature after turbine

m3/min [cu.ft/min]

8

10,4

13,3

16,4

17,3

Heat rejection the surrounding

Heat rej. from engine to surrounding

kW [BTU/min]

2,4

3,3

4

5,3

5,9

Engine water circuit

Engine water circuit capacity

11 liters [2,9 US gal]

Raw water circuit

Heat rejection to raw water

kW [BTU/min]

28,5

40,5

55,1

72,2

79,7

Maximum permissible raw water temp to engine

41 oC [oF]

Maximum temperature increase across fresh water circuit of engine

oC [oF]

5

6

8

11

12

Maximum permissible test pressure

100 kPa [402 in H2 O]

Raw water capacity

3 liters [0,79 US gal]

Raw water flow

7,8 m3/h [275 cu.ft/h]

Maximum pressure head

100 kPa [402 in H2 O]

Highest permissible suction head

20 kPa [80,4 in H2 O]

Highest permissible pressure drop over external raw water circuit

50 kPa [201 in H2 O]

Power take off[Look in technical data for propulsion](#)**Power Standards**

The engine performance corresponds to ISO 3046, BS 5514, DIN 6271 and in general SAE J 1349. The technical data applies to an engine operation on a fuel with calorific value of 42,7 MJ/ kg (18360 BTU/ lb) and a density of 0,84 kg/ liters (7,01 lb/ US gal, 8,42 lb/Imp gal), also where this involves a deviation from the standards.

Engine speed governor in accordance with ISO 3046/IV, class A1 and ISO 8528-5 G2 (G3 with electronic speed governor).

Rating Guidelines

ISO Standard Power for continuous operation with 10% overload capability for 1 hour of 12.